

F-2®

Industrial Warning Siren



UL Listed: Siren is UL listed to standard 464 (60G3).

100% Maintenance Free: Nothing to lubricate or maintain.

Mechanically produced sound: Stronger and further reaching than electronically produced sound.

Repair Parts Available: All parts of the siren are available should you encounter a problem

1 year Warranty: So you can rest assured we stand by our products.

Stainless Steel Version: **CRES 316 SS** available on special order for salt water environments.

mail @SentrySiren.com

866-427-4736

SENTRY SIREN Inc.®
PRODUCING THE WARNING SIRENS
HEARD 'ROUND THE WORLD SINCE 1905 ©



Tens of thousands of satisfied customers have used this siren in a wide range of industrial, municipal, and emergency signaling applications. Recently, the F-2 received full, Grade A Shock Approval by the U.S. Navy and is now standard equipment on all U.S. Navy Battleships. The F-2 employs a carefully machined and balanced aluminum fan and housing, and aluminum, powder coated projectors. The air intake is screened to protect against foreign matter. Corrosion protected, it is suitable for permanent outdoor installation.

The model F-2 tested at 117 dB. at 10 ft outdoor, 113 dB. at 10 ft. in an anechoic chamber, and at 103 dB(A) in a reverberant room to U.L. Standard 464. The model F-2 runs on 120 volt AC/DC power, with a running amperage of 2.5 amps. It can also be ordered in 240/250 AC/DC. With the mounting bracket in the upright position, the F-2 is 15 3/8" long, and 8 1/2" in diameter at its widest point. Shipping weight is 11 pounds.

The Ultimate Utility Siren !!!

2812 N. 9th St.
P.O. Box 386
Canon City, CO 81212

www.SentrySiren.com

Phone: 866-427-4736 (866-4-A-SIREN)
Fax: 719-269-3397
E-mail: mail@SentrySiren.com